

# Composite Install Kit



## Features & Benefits

- Composite Install Kit includes everything a fitter requires to install a Composite Worktop. There are also products for Care & Maintenance included that can be used after installation and should be passed onto the customer.

The kit includes the following:

Installation and Care & Maintenance Guide –  
**Detailed instructions of how to install and care for your composite worktop. Note: Follow the Worktop Manufacturer Installation Guidelines in the first instance.**

Self Adhesive Heat Reflective Foil Sheets x2 –  
**For use on the underside of the worktop above dishwasher, cooker and washing machine. Necessary to stop the heat from cracking the worktop.**

Heat Reflective Tape Roll –  
**For worktop hob cut outs. Necessary to stop the heat from cracking the worktop.**

Abranet Sanding Disc 100, 150 & 220 grit –  
**Use to sand the worktop joint once adhesive has been applied.**

Biscuits (4 wooden) –  
**Fit biscuits in the worktop joint to make sure it remains level once installed.**

Butterfly Bolt x6 –  
**Joint worktops together using three bolts per standard 600mm joint.**

Fixings Pack (12 brackets / 48 screws & washers) –  
**Fix Solid Surface worktops at intersection with carcass tops. Expansion brackets allow movement of worktop.**

Alcohol Wipes x2 –  
**Clean the worktop joint before applying adhesive to make sure there are no loose particles in the joint.**

Solid Surface Rejuvenate –  
**Use to remove persistent stains, scratches and to generally renovate your worktop if looking scratched and dull.**

Solid Surface Worktop Cleaner –  
**Use for everyday cleaning of the work surface and for the final clean after installation.**

Disposable Gloves –  
**Use when applying adhesive and Solid Surface Repair Cream - always wear rubber gloves when using chemicals**

Sanding Foam Pad 180 Grit –  
**Use on severe stains.**

Abrasive Disc Pad White, Grey and Maroon –  
**Use on minor scratches and stains. Also use to finish the worktop joint after the sand papers have been used.**

Microfibre Cloth –  
**Use with Solid Surface Worktop Cleaner for everyday cleaning.**

ColorSeam Solid Surface Adhesive –  
**Use colour matched adhesive to create a seamless joint.**

Cartridge Gun Adapter –  
**Use with a regular cartridge gun to dispense the ColorFill Solid Surface Adhesive.**



## UNIKA COLOR PRODUCTS LTD

Unika House, New York Way, New York Industrial Park, Newcastle upon Tyne, U.K. NE27 0QF

Telephone: +44 (0) 191 259 0033

Fax: +44 (0) 191 257 4525

Email: sales@unika.co.uk www.unika.co.uk



The mark of responsible forestry



PEFC® 16-33-1158



ISO 14001



OHSAS 18001



ISO 9001

# Composite Install Kit

## Solid Surface Rejuvenate

**Use on:** Corian & Acrylic Worktops

### Features:

- Solid Surface Rejuvenate will renovate acrylic and polyester worktops for example, Corian, Slab Tech, HI-MAC'S, Earthstone, Avonite etc.
- It is designed to remove minor scratches from solid surface worktops and leave the worktop as good as new. Solid Surface Rejuvenate contains mild abrasive particles which when coupled with a white nylon pad will buff up the work surface.
- Use as and when required on worktop areas that are subjected to a lot of wear and tear. Or use to renovate your whole top when it becomes scratched and dull.
- Unika Solid Surface Rejuvenate is a ready to use specialist cleaner that will renovate the work surface safely.

### Directions:

- Shake well before using.
- Apply cream over the affected area of work surface.
- With the use of a white nylon pad, polish the Repair Cream into the surface using a circular motion. If necessary polish over the whole work surface.

Always use the least abrasive pad possible to remove marks. Start with the white pad, rubbing the stain in a circular motion. If this is ineffective, progress to the more abrasive Grey Pad and finally the Maroon Pad. Always finish by using the White Pad in conjunction with Unika Solid Surface Worktop Cleaner.

- Clean the residue with a clean cloth and spray the affected area with Unika Solid Surface Worktop Cleaner and wipe off with a microfibre cloth.
- For the most severe stains, it may be necessary to use the light grey sanding pad. Remove the scratch then complete the sanding process. Use a maroon abrasive pad, followed by a grey abrasive pad and finish with a white pad and Solid Surface Rejuvenate.

## Solid Surface Worktop Cleaner

**Use on:** Corian & Acrylic Worktops

### Features:

- Unika Solid Surface Worktop Cleaner is a ready to use everyday specialist cleaner, which tackles everyday grease and grime.
- Antibacterial care
- Cleans worktop safely – it is non hazardous, biodegradable and solvent free
- Cleans worktops without leaving smears to a sparkling clean finish.

### Directions:

- Spray directly onto work surface. Use a clean dry soft cloth to dry surface and buff to a finish.
- It is always best to clean up spills as they occur. However if any stains need further attention, allow Unika Solid Surface Cleaner 30 seconds contact time before wiping and rinsing.

## ColorSeam Solid Surface Adhesive

### Features:

- Unika ColorSeam is a revolutionary two component Methyl Methacrylate that will provide a colour matched seamless look for Solid Surface Worktops.
- It can be used on Solid Surface and Composite Worktops made from Acrylic and Acrylic/Polyester blends for example – Corian, HI-MAC'S, Slab Tech, Earthstone, Avonite etc.
- It is available in a range of popular standard colours. We specialise in small batch production for special colour runs.
- Unika ColorSeam has an advanced non-stain colour system.
- Once cured the bond line is UV stable and has very high chemical and moisture resistance.
- It can be used for jointing kitchen and bathroom worktops. It can be used in laboratories, on reception counters, tables, hotel rooms etc.

## UNIKA COLOR PRODUCTS LTD

Unika House, New York Way, New York Industrial Park, Newcastle upon Tyne, U.K. NE27 0QF

Telephone: +44 (0) 191 259 0033

Fax: +44 (0) 191 257 4525

Email: sales@unika.co.uk www.unika.co.uk



The mark of responsible forestry



PEFC/16-33-1158



ISO 14001 001



OHSAS 18001 001



ISO 9001 001

# Composite Install Kit

## Directions:

1. For full User Instructions please see the 'Solid Surface Installation Components Booklet'.
2. Ensure both sides of the joint are perfectly matched and use alcohol wipes to clean the joint, allow to dry.
3. Mitre the worktop, fit connecting bolts and cut biscuit slots ready for installation.
4. Apply a continuous bead of ColorSeam along the full length of the top and bottom edge of the joint and front of the downturn. Apply also to the biscuits slots before putting the biscuits in place. Push the two parts of the worktop together.
5. Apply a second continuous bead of Adhesive to the top edge of the joint and fill the joint ensuring that sufficient adhesive is used so that when the sheets are brought together, a continuous bead of adhesive flows out of the joint area.
6. Tighten up the worktop bolts, checking for alignment.
7. Allow the adhesive to cure to a hard rubber consistency, approx 30 minutes.
8. Remove glue deposits on the surface with a wide sharp chisel taking care not to damage the worktop. Complete with the sanding process outlined in the 'Installation Components Booklet'.

## Retailer Opportunity:

Sell alongside every Solid Surface Worktop Sale.

A good quality Worktop Cleaner and Repair Cream is necessary to maintain a Solid Surface worktop.

## UNIKA COLOR PRODUCTS LTD

Unika House, New York Way, New York Industrial Park,  
Newcastle upon Tyne, U.K. NE27 0QF

Telephone: +44 (0) 191 259 0033

Fax: +44 (0) 191 257 4525

Email: sales@unika.co.uk www.unika.co.uk



The mark of responsible forestry

